



ECW120



Cloud Managed 11ac Wave 2 Indoor Wireless Access Point

Delivers higher speeds and user capacity and supercharges performance faster than 11ac Wave 1 APs

Product Highlights

EnGenius Cloud Managed ECW120 Beamforming Wi-Fi 802.11ac Wave 2 Indoor Access Point delivers 1.3 Gbps speeds and higher user capacity. It supercharges performance up to 30% faster than legacy 11ac Wave 1 APs. This dual-band AP with MU-MIMO and Beamforming features meshing, supports PoE, and improves connection reliability for business-class Wi-Fi.

Features & Benefits

- Dual-radio 2x2 802.11ac/a/b/g/n with MU-MIMO & Beamforming technology
- Supports up-to 867 Mbps in 5-GHz band & 400 Mbps in 2.4-GHz band
- Compliance with 802.3af & 48V PoE input for flexible installation up-to 328 feet
- Quick-Scan Device Register & Configuration and Remote Monitoring & Troubleshooting
- Cloud Manage unlimited number of AP's from Anywhere with the EnGenius Cloud App



LED Indicators

- 1 x Power
- 1 x LAN
- 1 x 2.4 GHz
- 1 x 5 GHz
- 1 x Mesh (ECW120)

Power Source

- Power-over-Ethernet: 802.3af Input
- IEEE 802.11e Compliant Source
- 12VDC /2A

Maximum Power Consumption

- 12W

Operating Frequency

- Dual-Radio Concurrent 2.4 GHz & 5 GHz

Wireless & Radio Specifications Operating Frequency

- Dual-Radio Concurrent 2.4 GHz & 5 GHz

Operation Modes

- Manage Mode: AP, AP Mesh

Frequency Radio

- 2.4 GHz: 2400 MHz ~ 2472 MHz
- 5 GHz: 5150 MHz ~ 5250 MHz, 5250 MHz ~ 5350 MHz, 5470 MHz ~ 5725 MHz, 5725 MHz ~ 5850 MHz

Standards

- IEEE 802.11b/g/n on 2.4 GHz
- IEEE 802.11a/n/ac Wave 2 on 5 GHz

Antenna

- 1 x 2.4 GHz: 5 dBi
- 1 x 5 GHz: 5 dBi
- Integrated Omni-Directional Antenna

Physical Interface

- 1 x 10/100/1000 BASE-T, RJ-45 Ethernet Port
- 1 x DC Jack
- 1 x Reset Button

Transmit Power

Up to 23 dBm on 2.4 GHz

Up to 23 dBm on 5 GHz

Tx Beamforming (TxBF)

Radio Chains/Spatial Stream

2x2:2

SU-MIMO

Two (2) spatial streams Single User SU-MIMO for up to 400 Mbps wireless data rate with VHT40 bandwidth to a 2x2 wireless client device under the 2.4GHz radio. Two (2) spatial stream Single User SU-MIMO for up to 867 Mbps wireless data rate with VHT80 to a 2x2 wireless device under the 5GHz radio.

MU-MIMO

Two (2) Spatial Streams MU-MIMO up to 867 Mbps wireless data rate for transmitting to two (2) streams MU-MIMO capable wireless devices under 5GHz simultaneously.

Supported Data Rates (Mbps):

2.4 GHz: Max 400

5 GHz: Max 867

802.11b: 1, 2, 5.5, 11

802.11a/g: 6, 9, 12, 18, 36, 48, 54

802.11n: 6.5 to 300 Mbps (MCS0 to MCS15) (Additional 25% bandwidth when enabling 256-QAM uner HT40)

802.11ac: 6.5 to 867 Mbps (MCS0 to MCS9, NSS = 1 to 2)

Supported Radio Technologies

802.11b: Direct-Sequence Spread Spectrum (DSSS)

802.11a/g/n/ac: Orthogonal Frequency-Division Multiplexing (OFDM)

802.11n/ac: 2x2 MIMO with 2 Streams

Channelization

802.11ac Supports Very High Throughput (VHT)—VHT 20/40/80 MHz

802.11n Supports High Throughput (HT)—HT 20/40 MHz

802.11n/ac Packet Aggregation: AMPDU, ASPDU

802.11n Supports Very High Throughput (VHT) Under the 2.4 GHz Radio—VHT 40 MHz (256-QAM)

Supported Modulation

802.11b: BPSK, QPSK, CCK

802.11a/g/n: BPSK, QPSK, 16-QAM, 64-QAM

802.11ac: BPSK, QPSK, 16-QAM, 64-QAM, 256-QAM

Multiple BSSID

8 SSIDs on both 2.4GHz and 5GHz radios.

VLAN Tagging

Supports 802.1q SSID-to-VLAN Tagging

Cross-Band VLAN Pass-Through

Management VLAN

Spanning Tree

Supports 802.1d Spanning Tree Protocol

QoS (Quality of Service)

Compliant With IEEE 802.11e Standard

WMM

SNMP

v1, v2c, v3

MIB

I/II, Private MIB

Wireless Security

OWE

WPA2 Personal

WPA3 Personal (SAE) - WPA3 Only

WPA3/WPA2 Personal Mixed

WPA2 Enterprise

WPA3 Enterprise Suite B

Hide SSID in Beacons

MAC Address Filtering, Up to 32 MACs per SSID

Wireless STA (Client) Connected List

SSH Tunnel

Client Isolation

Environment & Physical Temperature Range

Operating: 32°F~104°F (0 °C~40 °C)

Storage: -40 °F~176 °F (-40 °C~80 °C)

Humidity (non-condensing)

Operating: 90% or less

Storage: 90% or less

Dimensions & Weight

Weight: 0.80 lbs. (362 g)

Diameter: 6.36" (161.5 mm)

Height: 1.64" (41.5 mm)

Package Contents

1 – ECW120 Cloud Managed Indoor Access Point

1 – T-Rail Mounting Kit

1 – Ceiling and Wall Mount Screw Kit

1 – Mounting Bracket

1 – Quick Installation Guide

Warranty

2 Year

Certifications

CE

FCC

IC