



# DAG2000-8S80 Hybrid Analog VoIP Gateway

## Overview

DAG2000 series hybrid analog gateway are versatile IP-based voice and fax gateway. For small business, the family office, remote office and branch businesses provide a low cost, simple operation VoIP solutions. FXS/FXO hybrid gateway support network failure and power failure lifeline feature, flexibly realize interoperability with simulation PBX and provide reliable voice quality assurance for the traditional voice transition to IP voice. Support standard SIP protocol and compatible mainstream IPPBX and soft switch platform.

## Pictures



Front



Back

## Key Features

- 8 FXS and FXO hybrid
- Flexible port group
- IP trunk
- Flexible routing and manipulation
- Data/ Voice/ Management VLAN
- Voice and FAX all in one
- Power and network failure lifeline
- Firmware update automatically /configure update

## Physical Interfaces

### Phone Interfaces:

8 FXS and 8 FXO, RJ-11

### Ethernet Interfaces:

3\* LAN 10/100Mbps

### Console:

1\* RS232, 115200bps

## FXS

Connector: RJ11

Dial Mode: DTMF and Pulse

Pulse: 10 and 20 PPS

Caller ID: DTMF/FSK CLI Presentation

Reversed Polarity

Programmable Call Progress Tone

Max Cable Length: 5 km

## FXO

Connector: RJ11

Dial Mode: DTMF/Pulse Dialing

Caller ID: FSK, DTMF

Polarity Reversal

Answer Delay

Busy Tone Detection

No Current Detection

## Voice & FAX

G.711A/U law, G.723.1, G.729A/B,

Silence Suppression

Comfort Noise Generation(CNG)

Voice Activity Detection(VAD)

Echo Cancellation(G.168), with up to 128ms

Adaptive (Dynamic) Jitter Buffer

Programmable Gain Control

T.38/Pass-through

Modem/POS

DTMF mode: Signal/RFC2833/INBAND

VLAN 802.1P/802.1Q

Layer3 QoS and DiffServ

### Shenzhen Dinstar Co.,Ltd.

Floor 18, Building 7A, Vanke Cloud City Phase 1, Xingke 1st Street, Xili Sub-district, Nanshan District, Shenzhen, P.R. China 518000

www.dinstar.com  
sales@dinstar.com



## VoIP

### Protocol:

SIP v2.0 (UDP/TCP),RFC3261

SDP,RTP(RFC2833), RFC3262,

3263,3264,3265,3515,2976,3311

SIP TLS/SRTP

RTP/RTCP, RFC2198, 1889

RFC4028 Session Timer

RFC3266 IPv6 in SDP

RFC2806 TEL URI

RFC3581 NAT,rport

Outbound Proxy

DNS SRV/ A Query/NATPR Query

SIP Trunk

Early Media/Early Answer

NAT:STUN, Static/Dynamic NAT

## Maintenance

SNMP v1/v2/v3

TR069

Auto Provisioning

Web/Telnet

Configuration Backup/Restore

Firmware Upgrade via Web

CDR

Syslog

Network Capture

NTP/Daylight Saving Time

IVR local Maintenance

Cloud-based Management

### About Us

Founded in 2011 in Shenzhen, DINSTAR is a leading global provider of IP Unified Communication products including VoIP Gateways, IP PBXs, IP Phones and SBCs, we have been delivering more agile, efficient and affordable communication solutions and unparalleled communication experiences to our customers with our reliable, innovative and future-proof products for years. Through our value-added distributors and resellers worldwide, now DINSTAR serves telecom operators, service providers, system integrators, enterprises, SMBs and OEM partners in over 100 countries.

## Network

Static/Dynamic IP,

PPPoE

DHCP Client

IPv4/IPv6

TCP, UDP,TFTP, FTP, ARP,RARP,

Ping, NTP, SNTP, HTTP/HTTPS, DNS

Ping / Tracert

DHCP Option 66,120,121

## Software Features

Port Group

Web ACL

Telnet ACL

Action URL

Digitmap

Routing Rules based Prefixes

Caller/Called Number

Manipulation

## Environmental

### Power supply:

100-240VAC,50-60Hz

**Power consumption(W):** 48W

Operator Temperature: 0 °C ~ 45 °C

Storage Temperature: -20 °C ~80 °C

Humidity: 10%-90% no condensation

Compliance: CE, FCC