

EAP102



INDOOR WI-FI 6 ACCESS POINT



INTRODUCTION

EAP102 is an enterprise-grade, concurrent dual-band Wi-Fi 6 indoor access point. EAP102 supports 5G 4 x 4 : 4 uplink and downlink MU-MIMO between the AP and multiple clients, with up to 2.9 Gbps aggregated data rate. EAP102 is equipped with Bluetooth Low Energy (BLE) radio enabling value-added applications such as iBeacon.

EAP102 can be operated as standalone mode or managed by Edgecore ecCLOUD and EWS-Series controller.



HIGHLIGHTS

- Concurrent Dual-Band 2.4GHz & 5GHz
- 802.11ax 4x4:4 UL MU-MIMO supporting up to 2.9 Gbps data rate
- Support up to 32 ESSIDs.
- Enterprise-Grade Wireless Security
- Bluetooth Low Energy (BLE) 5
- 802.3at Power over Ethernet (PoE)

SPECIFICATIONS

PHYSICAL	
Power	<ul style="list-style-type: none"> DC Input: 12V / 2.0A (Power adapter included) PoE: 802.3at compliant (PoE injector optional)
Dimensions (L x W x H)	<ul style="list-style-type: none"> 19.5 cm x 20.1 cm x 3.98 cm (7.68 x 7.91 x 1.57 in)
Weight	<ul style="list-style-type: none"> 0.7 kg (1.54 lbs)
Interface	<ul style="list-style-type: none"> Uplink: 1 x 10/100/1000/2.5GBase-T Ethernet, Auto MDIX, RJ-45 with 802.3at PoE LAN: 1 x 10/100/1000/2.5GBase-T Ethernet, Auto MDIX, RJ-45 Console: 1 x RJ-45 Port USB: 2 x USB 2.0 Port*¹
LED Indicator	<ul style="list-style-type: none"> Uplink / 2.4G-WiFi / 5G-WiFi / Power
Buttons	<ul style="list-style-type: none"> Restart/ Reset
Environmental Conditions	<ul style="list-style-type: none"> Operating Temperature: 0°C (32°F) to 45°C (113°F) Operating Humidity: 5% to 95% non-condensing
Power Consumption	<ul style="list-style-type: none"> 25W max*².
Antenna	<ul style="list-style-type: none"> Type: 4 x Built-in antenna (2.4 GHz & 5 GHz) Gain: 5.5dBi (2.4 GHz, BLE), 7.6 dBi (5 GHz)
Mounting	<ul style="list-style-type: none"> Wall/Ceiling/T-bar mount (Mounting kit included)
WI-FI	
Standards	<ul style="list-style-type: none"> 802.11ax (Wi-Fi 6) Concurrent dual-band 2.4 & 5 GHz
Supported Data Rates	<ul style="list-style-type: none"> 802.11b: 1, 2, 5.5, 11 Mbps 802.11a/g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps 802.11n: 6.5 –300 Mbps (20 / 40 MHz) 802.11ac: 6.5 –1733 Mbps (20 / 40 / 80 MHz) 802.11ax: 3.6 –574 Mbps (2.4 GHz, 20 / 40 MHz) 802.11ax: 3.6 –2400 Mbps (5 GHz, 20 / 40 / 80 MHz)
Radio Chains	<ul style="list-style-type: none"> 2.4 GHz: 2 x 2 5 GHz: 4 x 4
Spatial Streams	<ul style="list-style-type: none"> 2.4 GHz: 2; MU-MIMO support 5 GHz: 4; MU-MIMO support
Aggregate Conducted Transmit Power*³	<ul style="list-style-type: none"> 2.4 GHz: Up to 23 dBm*⁴ 5 GHz: Up to 26 dBm*⁴
Channelization	<ul style="list-style-type: none"> 2.4 GHz: 20 / 40 MHz 5 GHz: 20 / 40 / 80Mhz

*1: One USB port work at a time

*2: 22W when powered by DC

*3: RF output power aggregates across MIMO chains and doesn't contain antenna gain

*4: Maximum power is limited by local regulatory requirements


WI-FI	
Frequency Range	<ul style="list-style-type: none"> • 2.400 – 2.483 GHz • 5.150 – 5.850 GHz
Operating Channels	<ul style="list-style-type: none"> • 2.4 GHz: 1 –11 (US), 1 –13 (Europe), 1 –13 (Japan) • 5 GHz*5: 36 –165 (US), 36 –140 (Europe), 36 –144 (Japan)
ESSIDs	<ul style="list-style-type: none"> • Up to 16 per radio (32 total)
Certifications	<ul style="list-style-type: none"> • FCC, CE, LVD, NCC, BSMI, VCCI, JATE, TELEC, IC, C-Tick, Philippines, Thailand
PERFORMANCE	
Physical Data Rate	<ul style="list-style-type: none"> • Up to 574 Mbps (2.4 GHz) • Up to 2400 Mbps (5 GHz)
FEATURES	
Wireless	<ul style="list-style-type: none"> • 802.11 k/r • Orthogonal Frequency Division Multiple Access (OFDMA) • Client Isolation • Open Mesh
Network	<ul style="list-style-type: none"> • Spanning Tree Protocol (STP) • Dynamic Host Configuration Protocol (DHCP) • 802.1q • Access Control List (ACL) • Network Address Translation (NAT) • Dynamic VLAN • Link Layer Discovery Protocol (LLDP)
Security	<ul style="list-style-type: none"> • WPA-Personal (AES) • WPA-Enterprise (AES) • WPA2-Personal (AES) • WPA2-Enterprise (AES) • WPA3-Personal (AES) • WPA3-Personal Transition (AES) • WPA3-Enterprise (AES) • WPA3-Enterprise transition (AES) • MAC Address Authentication
Maintenance	<ul style="list-style-type: none"> • Network Time Protocol (NTP) • Standalone • Management by ecCLOUD • Management by EWS-Series Controller (Complete tunnel) • SSH • QR Code Onboarding • SNMP v2c • Remote Syslog
QoS	<ul style="list-style-type: none"> • RSSI Threshold (Optimal Client Filtering)
Others	<ul style="list-style-type: none"> • iBeacon

*5: Some channels are restricted by local regulatory requirements and certifications


SIGNAL COVERAGE PATTERN

Azimuth

■ 2.4 GHz/ BLE




■ 5 GHz




Elevation

■ 2.4 GHz/ BLE



■ 5 GHz



RECEIVE SENSITIVITY

Operating Mode	Data Rate	Receive Sensitivity (dBm)
802.11b	1 Mbps	-96
	11 Mbps	-88
802.11a	6 Mbps	-90
	54 Mbps	-72
802.11g	6 Mbps	-91
	54 Mbps	-75
802.11n (2.4 GHz/HT20)	MCS0	-90
	MCS7	-71
802.11n (2.4 GHz/HT40)	MCS0	-87
	MCS7	-68
802.11n (5 GHz/HT20)	MCS0	-89
	MCS7	-70
802.11n (5 GHz/HT40)	MCS0	-86
	MCS7	-67
802.11ac (VHT20)	MCS0	-90
	MCS8	-69
802.11ac (VHT40)	MCS0	-88
	MCS9	-64
802.11ac (VHT80)	MCS0	-85
	MCS9	-61
802.11ax (2.4 GHz/HE20)	MCS0	-92
	MCS11	-62
802.11ax (2.4 GHz/HE40)	MCS0	-89
	MCS11	-60
802.11ax (5 GHz/HE20)	MCS0	-90
	MCS11	-58
802.11ax (5 GHz/HE40)	MCS0	-87
	MCS11	-55
802.11ax (5 GHz/HE80)	MCS0	-85
	MCS11	-56