

EC-UP8P8C-SD-003-TR-1000

NETLAN Modular Plug RJ45/8P8C Cat. 5e (Class D), 100MHz, 3pinch, Universal Knife, for Conductor Thickness 0,47-0,51mm, Shielded, 1000pcs./bag

- ✓ Conductor diameter from 0.40 to 0.51 mm
- ✓ Gold plating contacts 3 mcd

Connectors EC-UP8P8C-SD-003-TR-1000 are designed for terminating single-core and multi-core 4 pair communication cables, can also be used to terminate 2 pairs of cables of both types of conductors. Connector made in shielded version and corresponds to category 5e. The connector housing is made of polycarbonate conforming to UL 94-V2.

It is delivered in individual packages of 100 pieces combined in a transport packaging containing 1000 pieces.



Basic equipment:
Plugs

1000 pcs

Manufacturer reserves the right to change external view and characteristics of product without reducing it's consumer properties

CHARACTERISTICS

P/N	EC-UP8P8C-SD-003-TR-1000
Category	5e
Bandwidth, MHz	100
Connector type	RJ45/8P8C
Connection style	Shielded
Contact plating	Gold, 3µinch
Diameter of conductors, AWG	25-26/0.40-0.51 mm
Type of conductors	Solid
Color	Transparent
Housing material	Polycarbonate, meets UL 94-V2
Temperature ranges	Storage from -25 to +55 °C. Operation from -25 to +55 °C
Warranty	1 year
Packaging	Polyethylene bag (1000 pcs.)

ORDERING TABLE

P/N	QTY	Cat.	Type	Color	Volume, m3	Weight, kg
EC-UP8P8C-SD-003-TR-1000	1000	5e	STP	Transparent	0.005963	2.400