

EC-UWO-1-UD2-WT-10 - 1 port

EC-UWO-2-UD2-WT-10 - 2 ports

Wall-Mbunt Outlet NETLAN, Cat. 5e (Class D), 100MHz, RJ45/8P8C, 110, T568A/B, Unshielded, White, 10pcs.

- ✓ Complete solution to install
- ✓ Best price

Wall outlets are supplied as a turnkey solution and are used to build simple home networks. Outlets will provide a quick and convenient connection of the subscriber to the information network.

Wall sockets use universal insert contacts (IDC) of the 110th type. Termination is also possible with the KRONE tool. The wiring is done according to two standards: T568A or T568B.

EC-UWO-1-UD2-WT-10 has 1 unshielded RJ45 / 8P8C category 5e port.

EC-UWO-2-UD2-WT-10 has 2 unshielded RJ45 / 8P8C category 5e ports.

All NETLAN sockets and connectors come packaged in 10 pieces with the possibility of joint re-equipment piece by piece.



Basic equipment:	EC-UWO-1-UD2-WT-10	EC-UWO-2-UD2-WT-10
Wall outlet	10 pcs.	10 pcs.
Modules	1pc. / socket	2pc. / socket
Contact covers	2pc. / socket	4pc. / socket
Wood screws	1pc. / socket	2pc. / socket
Double-sided stickers	1pc. / socket	1pc. / socket

Manufacturer reserves the right to change external view and characteristics of product without reducing its consumer properties

## CHARACTERISTICS

P/N	EC-UWO-1-UD2-WT-10	EC-UWO-2-UD2-WT-10
Number of ports	1	2
Port type	RJ45/8P8C	
Category	5e	
Bandwidth, MHz	100	
Execution	Unshielded	
Connector Coating Material	Gold (3 mcd)	
Type of IDC Contacts	110	
Layout diagram	T568A/B	
Permissible diameter of conductors	25-24 AWG (0,445-0,511 )	
Installation	Wall	
Color	White	
Compliance	Compliant with standards: ISO / IEC 11801, EN 50173 and TIA / EIA-568	
Supported Applications	10BASE-T, 100BASE-TX, 100BASE-T4, 1000BASE-T, ATM-25, ATM-51, ATM-155, 100VG-AnyLan, TR-4, TR-16 Active, TR-16 Passive	
Temperature ranges	Storage -40 to +70 ° C. Installation 0 to +50 ° C. Operating 0 to +70 ° C	
Warranty	1 year	

## ORDERING TABLE

P/N	Category	Number of ports	Group packing			Transport box		
			Qty	Volume, m3	Weight, kg	Qty	Size, mm	Weight, kg
EC-UWO-1-UD2-WT-10	5e	1	10	0,000609	0,260	50 packs	620x300x200	11,0
EC-UWO-2-UD2-WT-10	5e	2	10	0,001107	0,490	25 packs	420x330x270	13,5

Manufacturer reserves the right to change external view and characteristics of product without reducing it's consumer properties