


NMF-OA1MM-FN-SCU-SCU-BG-100

NIKOMAX optical fiber adapter, Multi-mode 50/125µm, SC/UPC-SC/UPC, full flange, simplex, beige, 100pcs

Optical fiber adapters are designed for connecting patch cords and cables terminated with the same type of connector. Adapters are installed in removable panels in optical patch panels and provide a reliable connection, as well as stable parameters of detachable connection.

The SC adapter is made of plastic of different colors for better visual identification of the adapter type. Beige is used to connect the connectors with UPC polishing and MM fiber type. Mounting of SC type adapters to removable panels in optical crossways is carried out using metal latches and screws.

Centering bushings are made of ceramic for all optical connecting adapters intended for single-mode fiber. All adapters are equipped with plugs for protection against dirt and dust.



NMF-OA1MM-FN-SCU-SCU-BG-100

Package Content

Optical fiber adapter

100 pcs

The manufacturer reserves the right to change the appearance and characteristics of the product, without reducing its consumer properties

Specification

PN	NMF-OA1MM-FN-SCU-SCU-BG-100
Fiber type	Multi Mode 50/125
Adapter type	SC
Polishing	UPC
Execution	Simplex
Corpus material	Plastic
Color	Beige
Central bushing material	Ceramics
Insertion loss, dB	≤0,2
Return loss, dB	≥50
Number of switching cycles	No less than 1000
Temperature ranges	Laying -40 to +85 ° C. Operation -40 to +85 ° C
Individual packing	Plastic bag
Warranty	1 year

Ordering Table

PN	Execution	Adapter type / Polishing	Fiber type	Individual packing	
				Volume, m3	Weight, kg
NMF-OA1MM-FN-SCU-SCU-BG-100	Simplex	SC/UPC - SC/UPC	MM		

The manufacturer reserves the right to change the appearance and characteristics of the product, without reducing its consumer properties