

NMF-RP12-BLANK-CT-MTP-1U-BK

Fiber Distribution Unit 19", MTP/MPO, modular, 12 Slots for CT cassette module , Sliding type, Black

- ✓ Sliding type
- ✓ High density installation
- ✓ Standard height: 1U

The NIKOMAX fiber distribution unit **NMF-RP12-BLANK-CT-MTP-1U-BK** has a standard height of 1U and allows you to install up to 12 distribution CT cassette modules, thereby providing up to 144 LC ports. FDU has 3 pull-out shelves that allow you to install up to 4 optical cassette modules. A hinged lid is located on the front for added protection. Cable entry is carried out on the rear wall.

This FDU is an excellent solution for data centers, provides high density and, due to its design, ease of installation and maintenance.

The cassette design is extremely convenient for installation and allows you to flexibly combine cassette modules with different types of fibers in one design.



NMF-RP12-BLANK-CT-MTP-1U-BK

Базовая комплектация:

FDU	1 pc.
Mounting bracket	2 pcs.
Mounting kit	1 pc.

Specification

Part number	NMF-RP12-BLANK-CT-MTP-1U-BK
Housing material	Steel
Type of installed module	NMF-CT12xxPA-MTPM-LCU-TR
Number of Slots for cassette	12
Design	Sliding type
Maximum number of ports	Up to 144 LC ports
Color	Black
Installation	19" Rack or Cabinet
Dimensions	482 x 455 x 44 mm
Temperature ranges	Storage from -20 to +65. Operation from -20 to +65
Packaging	Individual - Cardboard box
Warranty	1 year

Order Table

Part number	Color	Type	Individual packing	
			Volume, m3	Weight kg
NMF-RP12-BLANK-CT-MTP-1U-BK	Black	MPO/MTP	-	6.50

Additional Photos



Suitable Optical Cassette Module



NMF-CJ12M4PA-MTPM-LCU-TR
12 ports LC / UPC, MM 50/125, OM4



NMF-CJ12S2PA-MTPM-LCU-TR
12 ports LC / UPC, SM 9/125, OS2



NMF-CJ12M3PA-MTPM-LCU-TR
12 ports LC / UPC, SM 9/125, OS2