

NMF-WO4-BLANK-CS-WT

NIKOMAX fiber optical wall outlet enclosure

NMF-WO4-BLANK-CS-WT fiber rosette box is able to hold up to 4 subscribers. It is used as a termination point for the drop cable to connect with patch cable in FTTH indoor application. It integrates fiber splicing, termination, storage and cable connection in one solid protection box.

Features

- Dust-proof design with IP-45 Protection level.
- Integrated with splice cassette and cable management rods.
- Manage fibers in a reasonable fiber radius condition.
- Easy to maintain and extend the capacity.
- Suitable for the fusion splice or mechanical splice.
- Embedded type surface, easy for installation and removal.
- 4 ports cable entrance for patch cable.



NMF-WO4-BLANK-CS-WT

Set Content:

	NMF-WO4-BLANK-SC-WT
Box with cover	1 pc.
Screws	2 pcs.
Bolts	2 pcs.
Protection sleeves	4 pcs.

Specification

Part number	NMF-WO4-BLANK-SC-WT
Temperature ranges	Storage from -40 to +70 ° C. Installation from 0 to +50 ° C. Operation from -10 to +60 ° C
Warranty	1 year
Installation	Wall
Color	White
Dimensions (WxHxD), mm	100x80x30
Packaging	Individual - PE bag
The number of slots for adapters	4
Type of supported adapters	Simplex SC or duplex LC
Plastic material	ABS

Ordering Table

Product Number	Sockets	Type of supported adapters	Dimensions, mm	Weight	Packaging
NMF-WO4-BLANK-CS-WT	4	SC-4 Ports / LC-8 Ports	100x80x30	0.3kg	PE bag