



UniFi Protect Smart Flood Light



Smart managed floodlight with integrated motion detection and light sensor. Housed in a compact, sleek design for low profile mounting. Easily setup and configure the UP-FloodLight with the UniFi Protect App.

Mechanical

Dimensions	135 x 65 x 50 mm (5.31 x 2.56 x 1.97")
Weight	Without Mount: 216 g (7.62 oz) With Flat Wall Mount: 236 g (8.32 oz) With Angle Mount: 273 g (9.63 oz)
Enclosure Materials	Plastic, Metal
Mount Materials	Flat Wall Mount: Plastic Angle Mount: Plastic
Weatherproofing	IPX5

Hardware

Processor	24 Kc MIPS Processor at 650 MHz
Memory Information	64 MB DDR2
Management Interface	UniFi Protect
Networking Interface	10/100 Mbps RJ45 Ethernet Port
Max. Power Consumption	10.5W
Power Method	802.3af PoE
Power Supply	802.3af PoE, 48VDC, 0.22A Max
ESD/EMP Protection	Air: ± 8kV, Contact: ± 8kV
Button	Factory Reset
RF	Bluetooth 4.0
LEDs	R/B/W
Operating Temperature	-10 to 45° C (14 to 113° F)
Operating Humidity	20 to 80% Noncondensing
Certifications	FCC, IC, CE



Specifications are subject to change. Ubiquiti products are sold with a limited warranty described at www.ui.com/support/warranty

©2020 Ubiquiti Inc. All rights reserved. Ubiquiti, the Ubiquiti U logo, the Ubiquiti beam logo, UniFi, and UniFi Protect are trademarks or registered trademarks of Ubiquiti Networks, Inc. in the United States and in other countries. Apple and the Apple logo are trademarks of Apple Inc., registered in the U.S. and other countries. All other trademarks are the property of their respective owners.